


Cタイプ (ミリねじ) スチール製 三価クロメート処理



単位：mm									単位：本		単位：円		
ねじの呼び (外径 D)	品 番	全長 L	ねじ長さ ℓ	最大 取付物厚	穿孔径	アンカー 埋込み長さ	穿孔深さ	座金付ナット 二面幅 S	入数		標準価格 (税抜き)		
									小箱	大箱			
M 6	 C- 645	45	15	5	6.4	30	36 以上	10	50	800	66		
	 C- 660	60	20	20							79		
	C- 680	80	20	40							148		
M 8	C- 840	40	15	5	8.5	25	33 以上	12			400	79	
	 C- 850	50	20			15	35					43 以上	85
	 C- 860	60	25										93
	 C- 870	70	25	104									
	 C- 890	90	45	149									
	C- 810	100	35	55	187								
	M10	C-1050	50	20	6	10.5	30	40 以上		14		300	91
 C-1060		60	16	40			50 以上	98					
C-1070		70						127					
 C-1080		80			26			149					
 C-1090		90	36		169								
 C-1010		100	46		193								
C-1012		120	66		227								
C-1015		150	96		310								
M12	C-1260	60	20	6	12.7	40	52 以上	19		30	240		
	 C-1270	70	16			50	62 以上				157		
	 C-1280	80									186		
	 C-1290	90		30							26	213	
	 C-1210	100	40	36							250		
	 C-1212	120	50	56							315		
	C-1215	150		86							384		
	M16	C-1680	80	30							10	17.0	50
 C-1610		100	40	20	60	76 以上	374						
 C-1612		120		40			441						
 C-1615		150		70			562						
 C-1619		190	50	110			716						
M20	C-2010	100	40	15	21.5	60	80 以上	30		10	40		
	 C-2013	130	50	25		80	100 以上		821				
	 C-2015	150		45					1,120				
	 C-2019	190		85					1,310				
	 C-2023	230		125					1,620				

・座金付ナット仕様

・最大取付物厚＝全長－埋込長さ－座付ナット高さ

Cタイプ (インチねじ) スチール製 三価クロメート処理

単位: mm									単位: 本		単位: 円
ねじの呼び (外径 D)	品 番	全長 L	ねじ長さ ℓ	最大 取付物厚	穿孔径	アンカー 埋込み長さ	穿孔深さ	座金付ナット 二面幅 S	入数		標準価格 (税抜き)
									小箱	大箱	
W5/16	C- 2550	50	20	5	8.5	35	43 以上	12	50	800	96
	C- 2570	70	25	25						400	114
W3/8	 C- 3060	60	25	6	10.0	40	50 以上	14		300	139
	 C- 3080	80		26							173
	 C- 3090	90	30	36							199
W1/2	C- 4070	70	25	6	13.5	50	62 以上	21	30	240	195
	C- 4090	90	30	26						180	262


・W5/16-W3/8 は、座金付ナット仕様

・W1/2 は、ナット / ワッシャー仕様

・穿孔深さ＝アンカー埋込み長さ＋アンカー外径分以上

・最大取付物厚＝全長－埋込長さ－座付ナット高さ または (ナット / ワッシャー)

SC タイプ ステンレス製 SUS304系



単位：mm									単位：本		単位：円
ねじの呼び (外径 D)	品 番	全長 L	ねじ長さ ℓ	最大 取付物厚	穿孔径	アンカー 埋込み長さ	穿孔深さ	ナット 二面幅 S	入数		標準価格 (税抜き)
									小箱	大箱	
M 6	 SC- 645	45	15	5	6.4	30	36 以上	10	50	800	187
	 SC- 660	60	20	20							231
	SC- 680	80		40							330
M 8	SC- 840	40	15	5	8.5	25	33 以上	12		400	190
	 SC- 850	50	20								15
	 SC- 860	60		25	25	255					
	SC- 870	70	45		308						
	 SC- 890	90	55	332							
	SC- 810	100	35	430							
	M10	SC-1050	50	20	6	10.5	30	40 以上			14
 SC-1060		60	25	16						326	
SC-1070		70		26	348						
SC-1080		80	30	36	440						
 SC-1090		90		46	473						
 SC-1010		100		66	550						
 SC-1012		120		96	627						
SC-1015		150			807						
M12	SC-1260	60	20	6	12.7	40	52 以上	19		30	240
	 SC-1270	70	25						16		
	 SC-1280	80		26		496					
	 SC-1290	90	30	36		660					
	SC-1210	100	40	56		704					
	SC-1212	120	50	86		825					
	SC-1215	150				972					
	M16	SC-1680	80	30		10	17.0		50		66 以上
 SC-1610		100	40	20	60	76 以上		1,166			
 SC-1612		120		40				1,298			
SC-1615		150	50	70				1,595			
 SC-1619		190		110				2,220			
M20	SC-2010	100	40	15	21.5	60	80 以上	30	10	40	1,800
	 SC-2013	130	50	25							2,145
	SC-2015	150		45		2,376					
	 SC-2019	190		85		3,220					
	 SC-2023	230		125		3,520					
	W3/8	 SC-3060	60	25		6	10.0			40	50 以上
W1/2	SC-4070	70	25	6	13.5	50	62 以上	21	30	240	640

- ・ M6・M16/W3/8 は、座金付きナット仕様
- ・ M20・W1/2 は、ナット/ワッシャー仕様
- ・ 最大取付物厚=全長-埋込長さ-座付きナット高さ または (ナット/ワッシャー)


316SC タイプ ステンレス製 SUS316系

単位: mm									単位: 本		単位: 円	
ねじの呼び (外径 D)	品 番	全長 L	ねじ長さ ℓ	最大 取付物厚	穿孔径	アンカー 埋込み長さ	穿孔深さ	ナット 二面幅 S	入数		標準価格 (税抜き)	
									小箱	大箱		
M 6	316SC- 645	45	15	5	6.4	30	36 以上	10	50	800	280	
M 8	316SC- 850	50	20	5	8.5	35	43 以上	13			360	
	316SC- 870	70	25	25							460	
M10	316SC-1060	60	25	6	10.5	40	50 以上	17		400	490	
	316SC-1080	80		26							660	
	316SC-1010	100		30							46	300
M12	316SC-1270	70	25	6	12.7	50	62 以上	19	30	240	730	
	316SC-1290	90	30	26						180	990	
M16	316SC-1610	100	40	20	17.0	60	76 以上	24	15	90	1,750	
	316SC-1612	120		40						1,950		

- ・ ナット/ワッシャー仕様
- ・ 最大取付物厚=全長-埋込長さ- (ナット/ワッシャー)

C-Dタイプ スチール製：溶融亜鉛めっき(ドブめっき)

芯棒：シルバービック処理



単位：mm

単位：本

単位：円

ねじの呼び (外径 D)	品 番	全長 L	ねじ長さ ℓ	最 大 取付物厚	穿孔径	アンカー 埋込み長さ	穿孔深さ	ナット 二面幅 S	入数		標準価格 (税抜き)
									小箱	大箱	
M 8	 C- 850D	50	20	5	8.5	35	43 以上	13	50	800	122
	 C- 870D	70	25	25						148	
M10	 C-1050D	50	20	6	10.5	30	40 以上	17		400	150
	 C-1060D	60	25								160
	 C-1080D	80		26		300	192				
	 C-1090D	90	36	236							
	 C-1010D	100	30	46			265				
	 C-1012D	120		66			200			309	
M12	 C-1260D	60	20	6	12.7	40	52 以上	19	30	240	247
	 C-1270D	70	25								270
	 C-1290D	90	30	26		50	62 以上			180	323
	 C-1210D	100	40	36							372
	 C-1212D	120	50	56							120
M16	 C-1610D	100	40	20	17.0	60	76 以上	24	15	90	565
	 C-1612D	120		40							671
	 C-1615D	150	50	70						60	892
M20	 C-2013D	130	50	25	21.5	80	100 以上	30	10	40	1,080
	 C-2015D	150		45							1,360
	 C-2019D	190		85							1,460

・ ナット / ワッシャー仕様

・ 最大取付物厚 = 全長 - 埋込長さ - (ナット / ワッシャー)