



IT タイプ スチール製 三価クロメート処理

単位：mm											単位：本		単位：円						
ねじの呼び	品 番	全長 L	首下長さ	ねじ長さ ℓ	はさみ込み厚	座金付き ナット 高さ	プレート 長さ C	座金付きナット 二面幅 S	施工時必要 中空幅	穿孔径	入数		標準価格 (税抜き)						
											小箱	大箱							
M 6	IT- 630	30	23	13	10～12	6.5	24	10	26	7.5	50	800	107						
	IT- 640	40	33	23	10～22								108						
	IT- 650	50	43	33	10～32								113						
M 8	IT- 835	35	27	15	12～13	8.5	30	12	32	9.0		400	110						
	IT- 840	40	32	20	12～18								112						
	IT- 845	45	37	25	12～23								116						
	IT- 850	50	42	30	12～28								117						
	IT- 855	55	47	35	12～33								117						
	IT- 860	60	52	40	12～38								122						
	IT- 865	65	57	45	12～43								125						
	IT- 870	70	62	50	12～48								129						
	IT- 875	75	67	55	12～53								130						
	IT- 880	80	72	60	12～58								133						
	IT- 890	90	82	60	22～68								139						
	IT- 810	100	92	70	22～78						144								
	M10	IT-1050	50	40	26						14～23		10.4	36	14	38	11.0	300	139
		IT-1070	70	60	46						14～43								155
IT-1090		90	80	66	14～63	184													
IT-1010		100	90	76	14～73	190													
M12	IT-1250	50	38	23	15～20	12.3	37	19	39	13.5	30	180	221						
	IT-1270	70	58	43	15～40								242						
	IT-1210	100	88	73	15～70								244						
W3/8	IT-3050	50	40	26	14～23	10.4	36	14	38	11.0	50	300	139						

・座金付きナット仕様

IT-S タイプ ステンレス製 本体 : SUSXM7 / プレート部 : SUS304 系

単位：mm											単位：本		単位：円
ねじの呼び	品 番	全長 L	首下長さ	ねじ長さ ℓ	はさみ込み厚	座金付き ナット 高さ	プレート 長さ C	座金付きナット 二面幅 S	施工時必要 中空幅	穿孔径	入数		標準価格 (税抜き)
											小箱	大箱	
M 6	IT- 630S	30	23	13	10～12	6.5	24	10	26	7.5	50	800	160
	IT- 640S	40	33	23	10～22								165
	IT- 650S	50	43	33	10～32								170
M 8	IT- 840S	40	32	20	12～18	8.5	30	12	32	9.0		400	220
	IT- 850S	50	42	30	12～28								230
	IT- 860S	60	52	40	12～38								240
	IT- 870S	70	62	50	12～48								250
	IT- 880S	80	72	60	12～58								260
	IT- 890S	90	82	60	22～68								270
	IT- 810S	100	92	70	22～78						280		
M10	IT-1050S	50	40	26	14～23	10.4	36	14	38	11.0	300	300	
	IT-1070S	70	60	46	14～43							330	
	IT-1090S	90	80	66	14～63							350	
	IT-1010S	100	90	76	14～73							360	
M12	IT-1250S	50	38	23	15～20	12.3	37	19	39	13.5	30	180	420
	IT-1270S	70	58	43	15～40								460
	IT-1210S	100	88	73	15～70								500
W3/8	IT-3050S	50	40	26	14～23	10.4	36	14	38	11.0	50	300	300

・座金付きナット仕様